and the second second second

EFFORTLESS**ZEROCLIENT**™

Optimized for VMWare, EffortlessZeroClient[™] is a powerful, secure, and easy-to-manage machine that eliminates the need for running, managing, maintaining, or securing enterprise desktops.



NEXT-GENERATION

The V1200 is powerful, secure and easy to manage. Our Zero Clients offer a seamless solution with dynamic features and a performance that will meet the needs of any environment.



SMALL FOOTPRINT

Our Zero Client only consumes between 6-12 watts of power, helping any organization lower their power consumption resulting in a much lower total cost of ownership.



SECURE

With no operating system, or local storage, our Zero Client provides an ultra-secure environment for your workforce.



IS SETTING UP AND USING EFFORTLESSZEROCLIENT™ COMPLICATED?

The EffortlessZeroClient[™] comes ready to plug in and go. It's as simple as logging into your EffortlessDesktop[™], and you're up and running.

A EffortlessZeroClient[™] comes with a keyboard, mouse and equipped with:

- Dual Monitor capability
- DVI-I
- DVI-D

MY ORGANIZATION HAS COMPLIANCE REGULATIONS TO ADHERE TO YOU. I SEE USB PORTS, HOW CAN THIS DEVICE FIT THESE NEEDS?

Effortless understands that every organization has different needs. While this device has the option to connect 4 USB 2.0 ports, these wouldn't bypass the users previously set privileges. This device also doesn't house any local data. If this device were to disappear, there wouldn't be any breaches of data.

IS THIS DEVICE EXPENSIVE?

EffortlessZeroClient[™] is much more cost effective than purchasing new laptops, desktops, etc. You can buy the device outright or pay a monthly charge.

EFFORTLESS**ZEROCLIENT** SPECIFICATIONS

- 1. Power On Indicator Light
- 2. Power Button
- 3. USB 2.0 (2)
- 4. Front Line Out
- 5. Mic In
- 6. USB 2.0 (2)

- 7. RJ45 LAN Port
- 8. DVI-D
- 9. DVI-I
- 10. Rear Line Out
- 11. DC Jack
- 12. Kensington Lock



TECHSPECS

MANAGEMENT UTILITY	Teradici Management
FORM FACTOR	Slime Line
PROCESSOR	Teradici PCoIP® Portal Processor - TERA2
CHIPSET	TERA2321 PCoIP®
DIMENSIONS	
DEVICE	5.12"(D) x 1.77"(W) x 5.91"(H) - 45mm x 150mm x 130mm
WEIGHT	1.54 lbs (0.70 kg)
CONNECTIONS	
PORTS	4 x USB 2.0, 1 x Mic In, 2 x Line Out, RJ-45 LAN, 1 x DC Jack
VIDEO/RESOLUTION	1 Monitor at 2560 x 1600* or 2 Monitors at 1920 x 1200, 1 x DVI-D + 1 x DVI-I

NETWORKING

ETHERNET FIBER

ENVIRONMENT

OPERATING TEMP. POWER Optional SFP Fiber Connector (100/1000Mbps)

32-104F (0-40C), 10-90% non-condensing humidity 7 Watts, DC-12V/3A External Power Adapter

CERTIFICATIONS

CE, FCC, CAN, ICES-3/NMB3, VCCI, UL, TUV-GS, C-TICK, GOST, BSMI, ROHS

10/100/1000 Base-T

Your company in the cloud. Effortlessly. WORK<ESS WORRY<ESS EFFORT<ESS FOR MORE INFORMATION CALL +1 (855) 363-6863